

IQC

Inline Quick Change Drinking Water System
Featuring the CeraCarb water filter

AquaCera
Doulton ceramic technology inside

The IQC Filter system was designed to remove the most commonly known contaminants whilst retaining water's valuable minerals essential for health and wellness.

This system incorporates an encapsulated CeraCarb filter inside the main body of the filter system allowing for easy servicing of replacement filters, no water spills to clean and an attractive alternative to standardized filter housings with a uniform appearance.

Water simply enters through the inlet side of the system forced through a series of stages including a 10 micron sediment wrap, 0.5 micron absolute rated Doulton® Sterasyl® sleeve and a matrix of bonded carbons and proprietary media blend to achieve reduction of most unwanted drinking water contaminants found in today's drinking water supplies.

IQC systems available:

- IQC-DIY includes standard faucet and installation kit
- IQC-DIY+ includes upgraded ceramic disc valve faucet in brushed nickel or polished chrome with installation kit

World renowned Doulton® ceramic filter technology with over 150 years of quality manufacturing experience

CeraCarb ceramic filters out:

- Pathogenic bacteria (cholera, typhoid, salmonella, E coli, etc.)
- Giardia, Cryptosporidium, and other parasites
- All types of particle contamination down to 0.5 Micron
- Removes chlorine, lead, taste, odor, VOC's, herbicides & pesticides
- Reduces Flouride, Arsenic, Mercury, Copper and Chromium



www.aquacera.com

CFCI
ceramic filters company inc

AquaCera® IIQC Filter System and Replacement Filters

Applications:

Commercial and Residential Drinking Water Systems
Pre and Post Reverse Osmosis Filtration
Water Coolers
Food Service

This In-Line water filter system is designed to be installed on a cold water supply line only. Maximum output of this filter is designed to be 1.0 GPM, under typical mains pressure of 60 psig to maintain proper filtration efficiencies, greater flow rate can cause damage to the filter inside and cause improper water filtration of contaminants.

Specifications:

Micron rating	0.5 absolute 100%
	0.2 micron >98%
Cyst, Cryptosporidium & Giardia	100%
Chlorine >95%	2000 Gallons @ 1.0 GPM
VOC's >95%	2000 Gallons @ 1.0 GPM
Lead Reduction >95%	1000 Gallons @ 1.0 GPM
Bacteriostatic	Silver-impregnated ceramic
Heavy Metals	>85% Reduction of Arsenic, Fluoride, Copper, Aluminum and Mercury
Filter Dimensions	3.125" O.D. x 2.875" I.D. x 12.7" L

Filtration efficiencies are based upon testing of components to NSF Standards 42 & 53 and other International water testing standards.

General Installation/Operation/Maintenance Requirements:

Flush new filter for 10 minutes prior to first use.
Replace cartridge annually for optimum results, flow rate will drop over time to indicate change frequency.
Install system in compliance with state and local laws and regulations.

Warnings:

Operating temperature 40-100° F.
Maximum operating pressure 120 psig.

Warranty Information:

CFCI warrants that the products delivered will be free from any defects in workmanship or materials. Further, the warranty provided herein applies only when used within the products specifications and service life, from the date of installation, beyond which time or use CFCI is absolved of any and all liability for any use of this product. In the event of a defect or non-conformity, buyer shall notify CFCI (or Authorized Dealer) in writing, supplying proof of purchase dates, installation dates, and will protect and retain the products for investigation, or liability is absolved from CFCI. There are no other warranties, either merchantability or fitness, either expressed or implied.